Van trailer CV300-L Sandwich

(EC0397TI)

Tiki van trailer is designed just for you if you need to protect your goods from the weather or prying eyes. A closed van helps keep your goods clean. It is good to use the outer sides of the trailer, for example, as an advertising surface for your products or services. The side panels are made of double laminated XPS insulated sandwich panel. The roof and front wall form a weatherproof unit with extremely low wind resistance. Leaf suspension with shock absorbers ensures a smooth ride even on uneven roads. It is easy to clean the bottom plywood with a water- and slip-resistant surface. The all-welded solution on the back panel ensures strong construction and longevity.

The tailgate can be opened in two directions - to the side and down.

This allows the tailgate to be used as a drive-up. By opening the hatch to the side, it is convenient to load goods with a forklift. The hatch, which is used as a driveway, is equipped with a special anti-slip surface coating and in addition, the hatch has gas shock absorbers that ensure smooth opening in the downward direction. The load capacity of the tailgate is 300 kg. The hatch also has a practical latch, which ensures that the side-opened hatch remains in place even in windy weather.

Upgrade your trailer with accessories for the best user experience.

Check out the product video



Tehnilised andmed

Furgooni sisemõõdud (PxLxH) (m):

Laadimiskõrgus (m):

Kasti laius (m): 1.5 3 Kasti pikkus (m): Raam: **Bolted** Täismass (kg): 750 Tühimass (kg): 425 Kandevõime (kg): 325 Haagise pikkus (m): 4.4 Haagise laius (m): 1 94 Sild: lehtvedru Pidurid: ΕI Rehvid: 155R13 M+S Rattapoltide arv:

Standardvarustus

- ✓ Tugevdatud kinnitusega tugiratas
- Küljele ja alla avanev gaasiamortisaatoritega varustatud tagaluuk
- ✓ Vastupidav keevissild 4-leheliste vedrudega
- Käepidemed mugavamaks manööverdamiseks
- Tugijalad
- 6 koormakinnitusaasa
- Tasakaalustatud rattad M+S rehvidega
- ✓ LED ääretuled
- ✓ LED sisevalgusti
- Pistik 13 klemmi



0.54